



# SPECIFICATION SHEET

## 16-150



### G-TEK® POLYKOR™ BLENDED SHELL WITH POLYURETHANE COATED SMOOTH GRIP

- Seamless construction offers increased comfort and breathability
- PolyKor™ blended shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Polyurethane coated palm and fingertips for great abrasion resistance, excellent puncture resistance and outstanding wet/dry grip
- Knit Wrist helps prevent dirt and debris from entering the glove
- Washable, resistant to chemicals, water, and ultraviolet light
- This style is also available tri-folded and shrink-wrapped for carefree dispensing through vending machines (16-150V)

### APPLICATIONS

- Electronics
- Glass cutting
- Sheet metal handling
- General duty
- Parts assembly
- Sharp small parts handling

### CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).

### TECHNICAL DATA

|              |  |                   |                   |                   |                   |                   |                    |
|--------------|--|-------------------|-------------------|-------------------|-------------------|-------------------|--------------------|
| MATERIAL     | Shell: PolyKor™ / Coating: Polyurethane                  |                   |                   |                   |                   |                   |                    |
| CONSTRUCTION | Seamless Knit  |                   |                   |                   |                   |                   |                    |
| COLOR        | Shell: ■ Salt & Pepper / Coating: ■ Gray                 |                   |                   |                   |                   |                   |                    |
| CUFF STYLE   | Continuous knit  |                   |                   |                   |                   |                   |                    |
| SIZES        | XS - XXXL  |                   |                   |                   |                   |                   |                    |
| PACKAGING    | 1 pair per polybag, 12 pairs per dozen, 6 dozen per case |                   |                   |                   |                   |                   |                    |
| CASE         | 16.7" x 11.2" x 11.2" / 42.5cm x 28.5cm x 28.5cm         |                   |                   |                   |                   |                   |                    |
| CASE WEIGHT  | XS   | S                 | M                 | L                 | XL                | XXL               | XXXL               |
|              | 7.7 lbs<br>3.5 kg  | 7.9 lbs<br>3.6 kg | 8.4 lbs<br>3.8 kg | 8.8 lbs<br>4.0 kg | 9.5 lbs<br>4.3 kg | 9.9 lbs<br>4.5 kg | 11.0 lbs<br>5.0 kg |
| COO          | China  |                   |                   |                   |                   |                   |                    |

### PERFORMANCE PROPERTIES

|               |                                 |   |   |   |   |   |
|---------------|---------------------------------|---|---|---|---|---|
| EN388: 4X42B  | ASTM F2992-15 ANSI Cut Level A2 |   |   |   |   |   |
| ABRASION      | 0                               | 1 | 2 | 3 | 4 | - |
| CUT           | X                               | 1 | 2 | 3 | 4 | 5 |
| TEAR          | 0                               | 1 | 2 | 3 | 4 | - |
| PUNCTURE      | 0                               | 1 | 2 | 3 | 4 | - |
| CUT (TDM-100) | A                               | B | C | D | E | F |




### BARCODES

| ITEM          | BAG          | DOZEN          | CASE           |
|---------------|--------------|----------------|----------------|
| ■ 16-150/XS   | 616314168314 | 01616314168313 | 02616314168312 |
| ■ 16-150/S    | 616314168291 | 01616314168290 | 02616314168299 |
| ■ 16-150/M    | 616314168284 | 01616314168283 | 02616314168282 |
| ■ 16-150/L    | 616314168277 | 01616314168276 | 02616314168275 |
| ■ 16-150/XL   | 616314168307 | 01616314168306 | 02616314168305 |
| ■ 16-150/XXL  | 616314168321 | 01616314168320 | 02616314168329 |
| ■ 16-150/XXXL | 616314168789 | 01616314168788 | 02616314168787 |

### DIMENSIONS (in/cm)

|          | XS        | S          | M          | L          | XL         | XXL         | XXXL        |
|----------|-----------|------------|------------|------------|------------|-------------|-------------|
| <b>A</b> | 7.5 / 19  | 8.3 / 21.0 | 9.1 / 23.0 | 9.4 / 24.0 | 9.8 / 25.0 | 10.0 / 25.3 | 10.6 / 27.0 |
| <b>B</b> | 3.3 / 8.5 | 3.5 / 9.0  | 3.7 / 9.3  | 3.9 / 10.0 | 4.1 / 10.3 | 4.1 / 10.5  | 4.3 / 10.8  |
| <b>H</b> | ■ Purple  | ■ Red      | ■ Yellow   | ■ Brown    | ■ Black    | ■ Blue      | ■ Gray      |



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: (800) 262-5755 • (518) 861-0133 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobal.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.